



CARDAN R WHITE

LL-9150-W

WHITE


Remote CONTROL GEAR

IP20

HOLE SIZE: 93mm ROUND

Cardan R is a high quality die-cast downlight made for professional applications. It features an adjustable, sealed and airtight lamp housing. It also features an adjustment mechanism which prevents airflow between the room and ceiling cavity, optimising thermal performance.

The Cardan R has been designed specifically for the Hero LED engines, with a specially engineered twist and lock system. The Hero Series of LED engines offers a variety of lumen packages, beam angles, colour temperatures and dimming protocols, while guaranteeing the service maintenance of the engine.



*Height with Super Hero Pro II

Light Source

LL-010-27-40	HERO ECO 9W 40D 27K CRI >90	9W	2700°K	40°	Ra90	500mA
LL-010-30-40	HERO ECO 9W 40D 30K CRI >90	9W	3000°K	40°	Ra90	500mA
LL-010-40-40	HERO ECO 9W 40D 40K CRI >90	9W	4000°K	40°	Ra90	500mA
LL-010-27-60	HERO ECO 9W 60D 27K CRI >90	9W	2700°K	60°	Ra90	500mA
LL-010-30-60	HERO ECO 9W 60D 30K CRI >90	9W	3000°K	60°	Ra90	500mA
LL-010-40-60	HERO ECO 9W 60D 40K CRI >90	9W	4000°K	60°	Ra90	500mA
LL-040-27-18	HERO XP 9W 18D 27K CRI90	9W	2700°K	18° 1110lm	Ra90	250mA
LL-040-27-24	HERO XP 9W 24D 27K CRI90	9W	2700°K	24° 1110lm	Ra90	250mA
LL-040-27-36	HERO XP 9W 36D 27K CRI90	9W	2700°K	36° 1110lm	Ra90	250mA
LL-040-27-60	HERO XP 9W 60D 27K CRI90	9W	2700°K	60° 1110lm	Ra90	250mA
LL-040-30-18	HERO XP 9W 18D 30K CRI90	9W	3000°K	18° 1140lm	Ra90	250mA
LL-040-30-24	HERO XP 9W 24D 30K CRI90	9W	3000°K	24° 1140lm	Ra90	250mA
LL-040-30-36	HERO XP 9W 36D 30K CRI90	9W	3000°K	36° 1140lm	Ra90	250mA
LL-040-30-60	HERO XP 9W 60D 30K CRI90	9W	3000°K	60° 1140lm	Ra90	250mA
LL-040-40-18	HERO XP 9W 18D 40K CRI90	9W	4000°K	18° 1220lm	Ra90	250mA
LL-040-40-24	HERO XP 9W 24D 40K CRI90	9W	4000°K	24° 1220lm	Ra90	250mA
LL-040-40-36	HERO XP 9W 36D 40K CRI90	9W	4000°K	36° 1220lm	Ra90	250mA
LL-040-40-60	HERO XP 9W 60D 40K CRI90	9W	4000°K	60° 1220lm	Ra90	250mA
LL-050-27-18	HERO XP 12W 18D 27K CRI90	12W	2700°K	18° 1470lm	Ra90	350mA
LL-050-27-24	HERO XP 12W 24D 27K CRI90	12W	2700°K	24° 1470lm	Ra90	350mA
LL-050-27-36	HERO XP 12W 36D 27K CRI90	12W	2700°K	36° 1470lm	Ra90	350mA
LL-050-27-60	HERO XP 12W 60D 27K CRI90	12W	2700°K	60° 1470lm	Ra90	350mA
LL-050-30-18	HERO XP 12W 18D 30K CRI90	12W	3000°K	18° 1520lm	Ra90	350mA
LL-050-30-24	HERO XP 12W 24D 30K CRI90	12W	3000°K	24° 1520lm	Ra90	350mA
LL-050-30-36	HERO XP 12W 36D 30K CRI90	12W	3000°K	36° 1520lm	Ra90	350mA
LL-050-30-60	HERO XP 12W 60D 30K CRI90	12W	3000°K	60° 1520lm	Ra90	350mA
LL-050-40-18	HERO XP 12W 18D 40K CRI90	12W	4000°K	18° 1570lm	Ra90	350mA
LL-050-40-24	HERO XP 12W 24D 40K CRI90	12W	4000°K	24° 1570lm	Ra90	350mA
LL-050-40-36	HERO XP 12W 36D 40K CRI90	12W	4000°K	36° 1570lm	Ra90	350mA
LL-050-40-60	HERO XP 12W 60D 40K CRI90	12W	4000°K	60° 1570lm	Ra90	350mA
LL-060-27-18	SUPERHERO XP 18W 18D 27K CRI90	18W	2700°K	18° 2110lm	Ra90	500mA
LL-060-27-24	SUPERHERO XP 18W 24D 27K CRI90	18W	2700°K	24° 2110lm	Ra90	500mA
LL-060-27-36	SUPERHERO XP 18W 36D 27K CRI90	18W	2700°K	36° 2110lm	Ra90	500mA
LL-060-27-60	SUPERHERO XP 18W 60D 27K CRI90	18W	2700°K	60° 2110lm	Ra90	500mA
LL-060-30-18	SUPERHERO XP 18W 18D 30K CRI90	18W	3000°K	18° 2180lm	Ra90	500mA
LL-060-30-24	SUPERHERO XP 18W 24D 30K CRI90	18W	3000°K	24° 2180lm	Ra90	500mA
LL-060-30-36	SUPERHERO XP 18W 36D 30K CRI90	18W	3000°K	36° 2180lm	Ra90	500mA
LL-060-30-60	SUPERHERO XP 18W 60D 30K CRI90	18W	3000°K	60° 2180lm	Ra90	500mA
LL-060-40-18	SUPERHERO XP 18W 18D 40K CRI90	18W	4000°K	18° 2400lm	Ra90	500mA
LL-060-40-24	SUPERHERO XP 18W 24D 40K CRI90	18W	4000°K	24° 2400lm	Ra90	500mA
LL-060-40-36	SUPERHERO XP 18W 36D 40K CRI90	18W	4000°K	36° 2400lm	Ra90	500mA
LL-060-40-60	SUPERHERO XP 18W 60D 40K CRI90	18W	4000°K	60° 2400lm	Ra90	500mA